CLAIMS

What is claimed is:

1. A method for forming a porous insulating layer, comprising:

the solution-applying step of applying a solution in which an insulating material is dissolved, onto a workpiece;

the solidified layer-forming step of forming a solidified layer by cooling the solution applied onto the workpiece to a temperature less than or equal to the melting point of a solvent contained in the solution;

the drying step of removing the solvent contained in the solidified layer to make the solidified layer porous; and

the firing step of hardening the porous layer obtained by the drying step.

- 2. The method for forming a porous insulating layer according to Claim 1, wherein, in the solution-applying step, the solution is applied so as to cover unevenness of the surface of the workpiece to flatten the surface of the applied layer.
- The method for forming a porous insulating layer according to Claim 1, wherein the drying step is performed under a reduced pressure.
- 4. The method for forming a porous insulating layer according to Claim 2, wherein the drying step is performed under a reduced pressure.

- 5. The method for forming a porous insulating layer according to Claim 1, wherein the solidified layer-forming step is performed after part of the solvent is removed from the solution applied onto the workpiece.
- 6. The method for forming a porous insulating layer according to Claim 1, wherein the firing step is followed by airtight treatment for eliminating the air permeability of the hardened porous solidified layer.
- 7. The method for forming a porous insulating layer according to Claim 1, wherein the solidified layer-forming step is performed by rapidly cooling the solution.
- 8. The method for forming a porous insulating layer according to Claim 1, wherein the application of the solution to the workpiece is performed by silt coating.
 - 9. A porous insulating layer-forming apparatus comprising:
- a solution-applying portion for applying a solution in which an insulating material is dissolved, onto a workpiece;
- a solidified layer-forming portion for cooling the solution applied onto the workpiece to a temperature less than or equal to the melting point of the solvent contained in the solution to form a solidified layer;

a vacuum drying portion for removing the solvent contained in the solidified layer by decompression to make the solidified layer porous; and a firing portion for hardening the porous layer obtained in the vacuum drying portion.

- 10. A porous insulating layer-forming apparatus according to Claim9, wherein the solidified layer-forming portion is provided in a decompressionchamber of the vacuum drying portion.
- 11. An electronic device including a porous insulting layer formed by the method for forming a porous insulating layer according to Claim 1.
- 12. An electronic device including a porous insulating layer formed by use of the porous insulating layer-forming apparatus according to Claim 9.